

সবথেকে এগিয়ে, সবাইকে ছাড়িয়ে। एक कदम आगे प्रगति। प्रगति के पथ पर चलें।

• High Productivity

• Sludge field reaper

• Super purity

• STD-III Compliance Engine



Marketed and Serviced in India By:

SS AGROTECH

Corporate Office :

22, Rabindranagar, Near Dunlop Gurudwara, Dunlop More,
Shop-2, Ground floor, Kolkata- 700108

Office Ph: 033 7962 5468, Contact: 9903410899 / 6291310004,

E-mail: e-procure@ssagrotech.in, web: www.ssagrotech.in



Model: 4LSZ-7.0

Application: Paddy

Type: Full-Feed Track Combine Harvester

TECHNICAL SPECIFICATIONS

Main Parameter:

No.	Item	Unit	Specifications
1	Model		4LSZ-7.0 AGRI ACHIEVER
2	Structure Type	/	Vertical Axis Flow Feeding Rubber Crawler Self-Prop.
3.	Engine	Type	STD-III, 4 Cylinder, vertical Engine, Water Cooled, DI Injection, Turbo Charged Engine.
		Rated Power	hp 113 hp
		Rotating Speed	r/min 2400 rpm
4	Dimension	Working State	mm 5450 X 2660 X 2850 (L x W x H)
5	Weight	kg	3600
6	Cutting With	mm	2450mm
7	Feeding Capacity	kg/s	5 / 7
8	Minimum Ground Clearance	mm	340
9	Operation Speed	km/h	1.8 to 5.3
10	Productivity	Acre/h	1 /1.5
11	Cutter Type	/	Standered Type II
12	Cutting Header Auguer Type	/	Telescopic Tranverse Conveyor Auger
		Type	Ecentrac Tooth (off center)
		Diameter	mm Ø 900
13.	Reel	Quantity	pc 5
		Quantity	pc 1
		Type	Vertical Axis Flow Spike Tooth
14	Threshing Roller	External (D x L)	mm Ø 620 x 2010
		Concave Sieve Type	/ Grid
16	Brake Type	/	Wet Frictions Plate
18	Rubber Crawler	Size	/ 550 X 90 X 56
		Track Gauge	mm 1265
19	Grain Tank Size	L	1600L / 1000 KG
20	Fuel Tank Size	L	180L
21	Gear Box	/	YD-85-1 Gearbox + (45CC HST)
22	Rethresher Type	/	Auger Spike Tooth
23	Grain Unloading Type	/	360° Unloading Auger.

* Upgradation / technical changes could be carried without prior information. SMS & AC Cabin unit available on request.

MSME
सूक्ष्म, लघु एवं मध्यम उद्यम
MICRO, SMALL & MEDIUM ENTERPRISES

